軟板開窗機 FPCB DIE CUTTING PRESS

用途:

軟性印刷線路板之成型與開窗。

特點:

■ 高剛性結構設計,可一片或多片沖剪, 成品美觀不起毛邊。

■構造簡單容易維修保養,容易架設刀模。

■簡易空壓設計,減少操作時所引起之噪 音及震動,樓上或樓下任何位置, 皆方便。

■高安全性操作設計,沒有操作恐懼感,男女操作皆適合。

APPLICATION:

For flexible printed circuit board punching & shaping.

FEATURES:

- With high rigidity structure design. It's able to punch single or multi pieces at the same time. Besides, the finished product looks fine and the cutting edge without burr problem.
- The structure is simple. And it's easy to repair, maintain and set the punch die.
- The simple pneumatic design. It could reduce the noise & vibration while machine running. Besides, it's convenient to be set on 1st floor, 2nd floor or any place.
- With high safe operation design. There is no any operating fear, and it is easy to handle by male and female operator.



規格表 SPECIFICATIONS

項目 Item 型號 Model	VACP-20
機台出力 Capacity (kgs)	Max:20000kg
工作台面積 Table area	610mm x 815mm
刀模可用面積 Applicable area of knife edge die (LxW mm)	450mm x 560mm
最大問距 Dayligh opening	50mm
行程 Stroke	30mm
操作速度 Operating speed (sec/cycle)	5~7 sec/cycle
所需空壓 Air pressure	6 kg/cm ²
空氣消耗量 Air consmption	40 liter/cycle
外型尺寸 Size of appearance (LxWxH mm)	1390 x 900 x 1500mm
電壓 Voltage V	single phase(單相)110v/220
重量 Weight (kgs)	1600kgs

活全機器股份有限公司

台中縣霧峰鄉五福路798號 NO. 798, Wu-Fu Rd., Wu-Feng Hsiang, Taichung Hsien, Taiwan. Tal:886-4-2331-3388 Fax:886-4-2331-3377 http://www.supvigor.com.tw E-mail:c.s.huang@seed.net.tw E-mail:sa-2@supvigor.com.tw

大陸辦事處

廣東省東筦市長安鎭新安社區新安二路9號 Tel:0769-2399-4598 Fax:0755-8149-0041 服務專線:13825252995

江蘇省蘇州市吳中區碧波街遠洋花園4單元307室 Tel:0512-6267-5616 Fax:0512-6513-8125 服務專線:13862422338

2010/05 @FASHION DESIGN 04-22338796